



Rustkote 943 & 945

Dewatering rust preventive fluid

Rustkote 943 and 945 are solvent deposited type rust preventive fluids with dewatering properties. Rustkote evaporates and leaves thin dry protective film on the applied surfaces. Drying time will vary according to film thickness and protection time required.

Benefits

- ◆ Rapid drying properties.
- ◆ High rust protective & dewatering performance
- ◆ Highly resistant to salt water and humidity
- ◆ Easy to remove by any types of hydrocarbon solvents
- ◆ Variety protection periods available
- ◆ Excellent demulsibility prolongs changing oil period.

Applications

- ◆ Rustkote are suitable for rust protection of manufactured components or parts as well as metal parts of machinery.
- ◆ Rustkote can be applied by dipping, spraying or brushing any dried parts and also parts passed coolant during machining process.

Degreasing

Hydrocarbon solvents such as white spirit, alkaline solutions or any common degreasing techniques, can remove film layer on the applied surface.

Typical Physical Characteristics	Rustkote 943	Rustkote 945
Appearance	Transparent Yellow	Transparent Yellow
Film Type	Oily film	
Flash Point °C	>45	>45
Density kg/l @ 15 °C	0.783	0.806
Oil film thickness Microns	3	5
Coverage (approx.) Square M/L	80	60
Protection Indoors	3	6
Protection Outdoors	-	3

Fluid Partnerships Making a World of Difference

THAI HOUGHTON 1993 CO., LTD.

7/109 Amata City Rayong Moo 4, Hwy. 331 T.Mabyangporn, A.Pluakdaeng, Rayong 21140

Tel: (6638) 956 109-15 Fax: (6638) 956 051 E-mail: Houghton@houghton.co.th

77/105-106 25th Flr., Sinn Sathorn Tower, Krungdhonburi Rd., Klongtonsai, Klongsarn, Bangkok 10600

Tel: (662) 440 1262-6 Fax: (662) 440 1267 E-mail: Houghton@houghton.co.th