

VBC RUSTOP P-DBH

Description

VBC RUSTOP P-DBH is the rust-preventive oil that can be used at room temperature.

RUSTOP P-DBH has also excellent water-displacement property and its soft film built on metallic and non-metallic surfaces is suitable for short-term, 1 month rust-prevention at indoor-storage due to excellent rust-protection property.

Benefits

1. Excellent rust-prevention property at low viscosity and thin layer film
2. Excellent water-displacement and water-separation property.
3. Easy degreasing by alkaline cleaner or solvent due to excellent degreasing
4. Excellent oil-stain protection in case of contacting each other at storage.

Properties

Contents	Results	Method
Appearance	Brown	Visual
Specific gravity, 15/4 °C	0.821	ASTM D 1298
Kinetic viscosity, 40 °C, cSt	2.300	ASTM D 445
Flash point, TAG, °C	50	ASTM D 92
Humidity cabinet test, hrs	480, A	KS M 2109
Salt spray test, hrs	36, A	KS M 2109

* Above test results are new fluid's typical properties, can be changed by quality improvement.

Application

RUSTOP P-DBH is applicable of methods written below:

Spray method at indoor and outdoor under normal temperature.

Brushing method at indoor and outdoor under normal temperature.

The parts and machinery coated RUSTOP P-DBH have to be sealed and stored as soon as possible after application.

Shelf Life

12 months from production date at sealed in room

The information contained and the recommendations made in this data sheet are based upon data collected and believed by us to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made herein with respect to the merchandise described and we assume no responsibility for the results or the use there of.