

VBC CI-4/SL 15W40

Description

VBC CI-4/SL 15W40 is the highest quality diesel engine oils formulated with the highest quality base oil Tri-Synthetic. It exceeds API CI-4 grade and meets European specification and most of other diesel engine maker's requirements. Its formulation of the best materials keeps the engine clean by reducing sludge and carbon build-up. Also, it is excellent in terms of noise reducing, wear protection and high output.

PERFORMANCE

Meets API CI-4/SL, ACEA E5/E7, MB228.3, 228.1, 229.1, Volvo VDS3,VDS2, MTU Type2,
 Mack EOM-Plus, Cummins CES 20076/20077, MAN 3275 performance requirements
 Excellent Engine Cleanliness, Wear Protection and Power Performance
 Soft Engin Standing Prevents Engine Parts Damage
 Minimized Carbon Sludge Production during Combustion
 Reduced Sediment Accumulation on Piston
 Preventing Friction and Abrasion of Engine
 Extended Engine Life, Noise Reduction and improved Power

Typical properties

Items	Results	Test method
Appearance, conc	Yellowish Brown transparent	VISUAL
Specific gravity, 15/4 °C	0.876	ASTM D1298
Viscosity (40 °C,mm ² /s)	106.7	ASTM D445
Viscosity (100 °C,mm ² /s)	14.189	
Viscosity index	135.0	ASTM D2270
Flash point, °C,COC	240.0	ASTM D92
Pour point, °C	-33.0	ASTM D97

* Above test results are new fluid's typical properties, can be changed by quality improvement.

Application

Heavy-duty truck/Bus with Diesel Engine
 Light Truck /SUV with Diesel Engine
 Passenger Car with Diesel Engine
 All Vehicles with Diesel Engine

Term of validity

1 year in room from the date of manufacture at sealed state, 0 to 40 °C.

The information contained and the recommendations made in this data sheet are based upon data collected and believed by us to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made herein with respect to the merchandise described and we assume no responsibility for the results or the use there of.