



GUMKYUNG VANS FB – 110L

Pressing oil

Attribute

VANS FB-110L is an excellent mineral stamping oil ,the key to promote the development and improvement of abrasion reduce the front end of the tool at a high film strength .

VANS FB-110L as a product, lubricity of the product boasts the highest performance in its class emulsion. Excellent load bearing performance of the **VANS FB-110L** extends the life of the mold, the sophistication of the processing surface.

Pax

Properties	VANS FB-110L	Remark
Appearance	Transparent colorless	Naked Eyes
Specific gravity (15/4°C)	0.8331	KS M 2002
Kinematic viscosity (40 ° C)	7.0 cSt	KS M 2014
Copper corrosion (100°C, 1hr)	2b	KS M 2018
Flash point (° C)	105°C	KS M 2056

Application

VANS FB-110L apply for automatic press and the general press, excellent drying performance.

VANS FB-110L apply for hard pressing with high thickness general forming .

VANS FB-110L suitable for alloy steel, stainless steel pull-out...

Performance Features and benefits:

- Give direction to the surface roughness and gloss of the machined parts also.
- The excellent extreme pressure lubrication and excellent workability and extend tool life
- The liquid crystal-clear and smells less.



Gumkyung Industrial

VANS WALD

Hwasung-City, Kyunggi-Do, R.O.KOREA
Tel: 031)354-2133 Fax: 354-2135

Packaging

VANS FB-110L is available in 20Litres in pail and 200Litres in drum.

Warranty

This information given here is considered to be correct and is offered for your consideration investigation and verification. No warranties are expressed or implied, since the use of our products is beyond our control. Statements concerning the use Gumkyung products are not to be construed as recommending the infringement of any patent.

VANS FB-110L is made in Korea