

NO-1 (SEWING OIL 7)

SEWING MACHINE OIL

Description

NO-1 is a high performance textile, knitting & sewing machines lubricant. Composition of VHVI base oil and selective additives to meet requirement of modern textile machines

Benefits

1. Low viscosity with light color and light odour
2. Good oxidation stability and multi-material compatibility
3. Low pour point and anti-foam characteristic.
4. Easy wash out & anti-stain properties
5. Effective surface weeting properties

Typical properties

Test items	Results	Test method
Appearance, conc	Bright & clear	VISUAL
Specific gravity, 15/4°C	0.82	ASTM D 1298
Kin. viscosity, 40°C, cSt	7.2	ASTM D 445
Kin. viscosity, 100°C, cSt	2.2	ASTM D 445
Viscosity index	110	ASTM D 2270
Flash point COC, °C	160	ASTM D 92
Pour point, °C	-32.5	ASTM D 97
Total acid number (mgKOH/g)	0.1	KSM 0065
Copper corrosion	1A	ASTM D 130

*The test results are typical properties of fresh oil, can be changed by quality improvement.

Application

Sewing machine, textile loom & machinery

Term of validity

12 months from the date of manufacture at sealed state, 0 to 40°C.

Safety

Refer to the our MSDS for safety information

The information contained and the recommendations made in this data sheet are based upon data collected and believed by us to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made herein with respect to the merchandise described and we assume no responsibility for the results or the use there of.